

SignBOX II



LED illumination for single or double-sided sign boxes

- 6500K is now 17% brighter
- Bright, even illumination
- Illuminates 125mm from face
- Mounted on flexible straps for easy installation
- Constant Current Technology (CCT)

Specifications

Part number:

Single-sided 6500K:	701946-6WS201
Single-sided 5000K:	701946-5WS201
Double-sided 6500K:	701946-6WD201
Double-sided 5000K:	701946-5WD201

Dimensions L x W x H: 216mm x 26mm x 8mm
60 modules per 6.1m chain

Viewing angle: 120°

LEDs per module: **Single-sided:** 3
Double-sided: 6

Modules per meter: 10

Coverage per row: 300mm

Optimal light throw: 125 to 300mm from face

Operating temperature: -40° C to +70° C

Protection class: IP66

Special feature: Cuttable in 100mm increments

Power per module: **Single-sided:** 0.9W

Efficacy:	Double-sided: 1.8W 6500K: 117lm/W 5000K: 100lm/W
Power capacity:	Per SloanLED 60W 12V DC power supply Single-sided: 60 modules Double-sided: 30 modules
Fastening:	Clamps with mechanical fasteners
Packaging:	60 modules per carton, 16 clamps included
Colour temperatures:	6500K, 5000K
Lumens per module:	Single-sided: 105 Double-sided: 210
Mounting hardware	Bracket (bag of 10): 401309-10 Clamp (bag of 16): 410155-16 Coupler (bag of 10): 401330-10



SignBOX™ II is covered by US and foreign patents pending.



Applelec: Appleby House, 15 Walker Terrace, Bradford, West Yorkshire BD4 7HP | **Tel:** 01274 774 477 | **Fax:** 01274 774 478
Email: sales@applelec.co.uk | **Website:** www.applelec.co.uk

